

Statement of Evidence:

H073

East Quarter Corner of Section 7, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

9" Blk Ash	S 18 E	28 links
9" Maple	S 58 W	22 links

1892 County Road Book, page 71, shows road laid by out Felix Parent on east-west 1/4 line.

1932 County Engineer's notebook No. 73 contains a road survey by H. G. Elletson for SAR No. 13. Corner is shown in 4-way road intersection with ties:

Elm	SE	57.5
NE Cor. Store	SW	49.4

1933 County Engineer's Notebook No. 72 contains survey of County road running north from this corner. Ties:

NE Cor. Store Found	SW	49.4'
PP	NE	52.4'

(Notation in 1963 shows these ties.)

1956 County Surveyor's Record Book 1, page 473, shows ties:

NE Cor. Store	SW	49.4
PP	NW	54.0

1959 County Engineer's Notebook No. 209 contains a road survey for CSAH No. 13 running east from this corner. Corner is shown as a hub set in 4-way road intersection with same ties as above.

1978 Ronald Engelmeyer, LS 13334, set a RR spike for the corner in intersection of roads north, east, and west. He filed a Certificate of Location (Doc. No. 151561) and shows a distance of 2652.53 feet south to the SE corner of Section 7.

2008 The County Surveyor's Office searched and found the RR spike as set by Ron Engelmeyer in 1978. Distance to the SE Corner measures 2652.43 ft. A tie to a PP NW measured 52.98 ft., which may be the same PP as referenced in 1956 (54 ft.). The tie to the NE Cor. Store referenced in 1933 was not found. The position falls on centerline of an east-west bituminous road (County Road 13) and centerline of a bituminous road to the north (County Road 82). The Surveyor accepts the position as the best evidence and set ties to same.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-156133.556
E-516227.209