

**Statement of Evidence:**

**H183**

East Quarter Corner of Section 18, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

9" Elm	S 50 E	20 links
12" W Ash	S 38 W	41 links

1980 Paul Wellen, LS 10461, noted corner at fence lines east-west and old road north-south with ties:

8" Twin Ash	NE	44.73'
8" Ash	SW	22.56'
8" Ash	W	10.14'

Measured 2646.01 feet to the NE corner of Section 18.

1994 David Regan, LS 12236, found a ½ " iron pipe lying over in swampy area on centerline of old township roadbed north-south and fence lines east-west. He straightened iron and filed a Certificate of Location (Doc. No. 1231250). (Tie to Ash SW is 22.38', which could be Wellen's tie).

2002 No resurvey information was found on this corner in the Benton County records.

2008 The County Surveyor's Office searched and found a ½" iron pipe as the same was reported by Regan in 1994. Distance to the NE Cor. measured 2646.73 ft., which agrees with Wellen's measurements in 1980. Ties were updated.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-150835.960

E-516098.765