

Statement of Evidence:

H343

East Quarter Corner of Section 34, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post with bearing trees noted as:

10" Elm	S 67 W	21 links
12" Blk Ash	N 42 E	6 links

No Date County Surveyor's Record Book 1, page 527, gives a distance of 2644.0 feet to the NE corner of Section 34.

- 1983 Sidney Williamson, LS 10918, found a 2" iron pipe 0.54 feet SW of a fence corner north/east/west. He filed a Certificate if Location (#168501).

- 1988 Paul Wellen's records, LS 10461, show a 2" iron pipe found and used.

- 2004 MN/DOT Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 134967.236
E- 531823.046

- 2008 The County Surveyor's Office searched and found a 2" iron pipe approximately 0.5 feet southwest of the corner of a north and east fence line, which checks with tie by Williamson in 1983. The position gives a distance to the NE corner of 2646.52 feet which agrees with the pre-1983 distance of 2644.0 feet. Position fits occupation and the Surveyor accepts the position as best evidence and updated ties. Coordinates to same agrees with those reported in 2004 above.