

**Statement of Evidence:**

**H011**

North Quarter Corner of Section 1, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Elm	S 76 E	15 links
18" W Oak	N 72 W	22 links

A line tree was noted as a 6" Sugar East 19.63 chains.

1914 County Engineers' Notebook No. 7, page 11, contains a road survey by M.J. Cleveland where survey ran east-west along town line. Notes show iron monument set. Stationing gives distance of 2668 feet to the NW corner of Section 1.

1921 County Engineers' Notebook No. 39 shows survey of road on town line. No mention is made of this corner with road run straight between section corners with a distance of 5325.5 feet for the mile.

1955 County Engineer's Notebook No. 202 shows a survey of SAR 5 running west to east on town line. Corner is shown marked by a spike set in center of road as a POT with town road south. Stationing gives distances of 2668.4 to the NW corner and 2654.7 feet to the NE corner. Ties:

PP	NW	32.15
Mailbox Post	SW	25.45

2006 The Benton County Surveyor's Office located the centerline intersection of east-west CSAH No. 5 and gravel township road to the south. We excavated the corner location and found no additional evidence. The corner was positioned on the centerline of the road south on line between the northeast and northwest corners of Section 1 as it was positioned in 1955.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-  
E-

2009 A 1/2-inch by 14-inch iron pipe capped 19552 was set to mark the obliterated corner position after road construction.