

**Statement of Evidence:**

**H261**

North Quarter Corner of Section 26, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

This corner is noted on the following recorded plats

<i>HENRICKS ADDITION</i> (CIM)	7/2/2001	Sidney Williamson
<i>FOLEY'S FIRST ADDITION</i>	9/27/1900	Felix Parent
<i>PARK LOTS ADDITION</i>	3/13/1915	J.P. Soderstrum

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

12" Blk Ash	N 28 W	37 links
9" Linden	S 61 ½ E	37 links

1912 County Engineer's notebook No. 2, page 35, contains a road survey by Cleveland that shows road laid out south and west of this corner. He measured south 5286 feet to the North ¼ corner of Section 35 and 2632 feet west to the NE corner of Section 27.

1988 Bruce Skipton, LS 17768, dug corner area with a backhoe and found a flat top stone down 3 feet at the centerline of a road north/south/west. He set a cast iron monument and filed a Certificate of Location (#191332).

2004 Westwood Professional Services, Inc. found the CIM. Measured 5287.62 feet to the North ¼ corner of Section 35 and 2632.80 feet to the NE corner of Section 27, which checked well with Cleveland's distances in 1912. CIM accepted as marking obliterated position.

County Coordinates Obtained by GPS to CIM:  
NAD 83 (1996 Adjustment)  
N- 142886.444  
E- 534556.482

2011 The Benton County Surveyor's Office set a 1/2-inch by 14-inch iron pipe capped 19552 at the position of the CIM, which was removed during construction of County Road No. 43.