

**Statement of Evidence:**

**H271**

North Quarter Corner of Section 27, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

|           |        |          |
|-----------|--------|----------|
| 9" Elm    | S 28 E | 29 links |
| 10" Maple | N 35 W | 17 links |

1991 William Lunser, LS 9394, set a  $\frac{1}{2}$ " I.P. near a fence line north/south/east/west. He filed a Certificate of Location (#234181) and notes a distance of 2665.02 feet to the NE corner Sec 28 and a distance of 2603.76 feet to the NE corner Sec 27 and a distance of 5320.14 feet to the North  $\frac{1}{4}$  corner Sec 34.

2002 No resurvey information was found on this corner in the Benton County Public Works records.

2003 Westwood Professional Services, Inc. searched corner area, but could not find the iron pipe set by Lunser. Found Lunser's ties and used ties to Ash trees west and south to set cast iron monument. Ash tree to the north had split and did not fit well. We measured 2665.50 feet to the NW corner and 2603.73 feet to the NE corner of Section 27. Accepted corner set by Lunser as marking the obliterated corner position.

County Coordinates Obtained by GPS to set CIM:

NAD 83 (1996 Adjustment)

N- 142954.885

E- 529320.410

2012 Benton County Surveyor's office found the cast iron monument set by Westwood in 2003. The location agrees with the coordinates of 2003 and is accepted as the obliterated quarter corner.