

Statement of Evidence:

H331

North Quarter Corner of Section 33, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

7" Blk Ash	N 69 E	12 links
7" Blk Ash	S 54 W	18 links

1910 Road Survey Report by Felix Parent, County Surveyor, shows survey beginning 550 feet west of this corner and running west along section line, with a total distance to the NW corner of 2680 feet.

1912 County Engineer's Notebook 1, pages 33-37 contains road survey by M.J. Cleveland for SR No. 10. Notes shows no stake found at occupation lines north and south. Stationing gives distances of 2691 feet to the NW corner and 2727 feet to the NE corner of Section 33.
(Also Engineer's Notebook 2, page 23)

1935 County Engineer's Notebook No. 87 contains a road survey for SAR No. 4 running from east to west. No corner is shown, but stationing shows $\frac{1}{4}$ line fence north south at 2721.6 feet from the NE corner and 2695.5 feet from the NW corner.

2001 Westwood Professional Services, Inc. found a spike at the intersection of the centerline of an east/west road and a tree line north.

2003 Westwood Professional Services, Inc. found spike and measured 2688.13 feet to the NW corner and 2719.60 feet to the NE corner of Section 33. The spike was found to be 1.48 feet south and 15.72 feet west of the lost position.

County Coordinates Obtained by GPS to spike:

NAD 83 (1996 Adjustment)
N- 137697.206
E- 523849.078

2004 MN/DOT replace spike with CIM.