

Statement of Evidence:

H341

North Quarter Corner of Section 34, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

18" W Oak	S 37 W	34 links
12" Elm	N 42 W	17 links

1912 County Engineer's Notebook 1, pages 33-37, contains road survey by M.J. Cleveland for SR No. 10. Notes shows fence north at assumed corner. Stationing gives distances of 2624 feet to the NW corner and 2654 feet to the NE corner of Section 34.

No Date County Surveyor's Record Book 1, page 527 gives a distance of 2640.46 feet to the NE corner of Section 34.

1983 David Regan, LS 12236, found a railroad spike with punch hole, 1.5 feet north of the centerline of CSAH No. 4 and filed a Certificate of Location (167988).

2003 Westwood Professional Services, Inc. found a cast iron monument in center of Co. Rd. 4 (east-west). We measured 2646.84 feet to the NW corner and 2646.97 feet to the NE corner of Section 34. It appears the CIM was set at the lost position. Did not find the ties listed on Regan's certificate and therefore don't know how the CIM relates to the RR spike he found. No record was found of who set the CIM.

County Coordinates Obtained by GPS (CIM)
NAD 83 (1996 Adjustment)
N- 137635.589
E- 529215.148

2004 MN/DOT
County Coordinates Obtained by GPS (CIM)
NAD 83 (1996 Adjustment)
N- 137635.633
E- 529215.156