

Statement of Evidence:

Northeast Corner of Section 12, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as: 1

2" W Ash	N 81 E	11 links
6" Blk Ash	N 41 W	20 links
8" Blk Ash	S 34 W	3 links
12" Blk Ash	S 3 E	23 links

A line tree was noted as a 6" Elm North 23.96 chains.

1912 County Engineer's Notebook No. 2, pages 49 and 50, contains a road survey for SR No. 14 by M. J. Cleveland. Survey runs north-south on section line. Notes show post at the corner with ties:

Fence West	30'	
8" Elm	S 16-30 E	82'

1941 County Engineer's Notebook No. 152 contains a road survey for CAR 32 running south to north on township line. Corner is shown marked by a spike set in center of road with intersection of town road east and west. Ties:

Cor. FP	SW	36.7'
Cor. FP	NW	41.1'

1963 County Surveyor's Record Book 1, page 483, notes a found iron with the following reference ties.

PP	SE	48.8
2 ND FP	SE	69.7
TP	NW	55.75

(Notation in Notebook No. 152: "Found piece of wood hub and placed iron with same ties.)

1992 Paul Wollen, LS 10461, found a RR Spike at centerline/centerline and replaced it with a cast iron monument. He filed a Certificate of Location (#216303). Tie to PP SE 48.73 feet agrees with 1963 tie.

2001 Westwood Professional Services, Inc. found a PK at centerline/centerline and found a cast iron monument 0.3 feet NE of PK.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-
E-