

Statement of Evidence:

H142

Northeast Corner of Section 14, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Tamarack	N 13 1/2 E	27 links
5" Tamarack	S 17 W	12 links

- 1901? County Surveyor's Record Book 1, page 485, and Record Book A, Map No. 34, shows a survey by John Whilt for Section 13 with a distance of 39.36 chains to the North 1/4 corner Sec 13 and a distance of 40.65 chains to the East 1/4 corner Sec 14.

- 2008 The County Surveyor's Office searched and found a 1/2" iron pipe capped 12236 33.00 ft. west of the centerline of a north-south gravel road (125th Ave NE). A further search to the west revealed a long standing fenceline running westerly toward the N 1/4 Cor. position. Projecting a line easterly through the old fenceline and iron pipe toward the point of centerline of said north-south road gives distances to the E 1/4 Cor. of Sec. 14 as 2681.63 ft. (40.63 ch.) and to the N 1/4 Cor. of Sec. 13 as 2597.31 ft. (39.35 ch.), which agrees well with Whilt's 1901 measurements. The corner is accepted as marking the obliterated position and ties were made.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-153738.798

E-537220.424