

**Statement of Evidence:**

**H182**

Northeast Corner of Section 18, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

24" Maple	S 58 W	7 links
18" Maple	S 61 E	28 links

1899 Road Survey Report by John E. Whilt, County Surveyor, shows survey running west to east on section line with a distance of 81.05 chains for the north line of Sec. 18. Road survey terminated 12.50 chains west of this corner, which is shown in an east-west cartway.

1977 William Lunser, LS 9394, set a ½ " iron pipe in centerline of road east-west and fence line north. He filed a Certificate of Location (Doc. No. 147078).

1980 Paul Wellen, LS 10461, measured 2646.01 feet to the East ¼ corner of Section 18.

1987 Paul Wellen measured 5241.13 feet to the NE corner of Section 19.

2008 The County Surveyor's Office searched and found a ½ " iron pipe as set by Lunser in 1977. Position falls along centerline of an east-west gravel road (95<sup>th</sup> St. NE) and on line with north-south tree lines. Distance to the NW Corner measures 5321.83 ft. (80.63 ch.), which falls 27.47 ft. (.42. ch.) short of Whilt's 1899 distance. Distances to the E ¼ Cor. of Sec. 18 and the NE Cor. of Sec. 19 measure 2646.73 ft. and 5241.45 ft., respectively, which agree with Wellen's measurements.

.

County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-153481.830  
E-516166.218