

Statement of Evidence:

H192

Northeast Corner of Section 19, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

13" Ash	S 5 1/2 W	10 links
11" Ash	N 6 3/4 W	19 links

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. Corner is shown as a spike set in center of road with SAR 11 south. Ties:

Cor. F.P.	SW	36.05'
F.P.	SE	28.85'

1987 Paul Wellen, LS 10461, found a 1/2 " iron pipe in road intersection, with roads running east, west, and south. He removed the iron pipe and set a cast iron monument. Filed Certificate of Location (Doc. No. 184288). Notes show measurements of 2639.75 feet to the North 1/4 corner of Section 20 and 5241.13 feet to the NE corner of Section 18.

2008 The County Surveyor's Office searched and found Wellens 1987 cast iron monument along the centerline intersections of east-west and north-south gravel roads. Ties from 1939 were not found. Distances to the N 1/4 Cor. of Section 20 and the NE Cor. of Section 18 give 2639.53 ft. 5241.45 ft., respectively, which agree with Wellens 1987 measurements. The corner is accepted as the best evidence. Ties were updated.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-148241.313
E-516067.331