

**Statement of Evidence:**

**H202**

Northeast Corner of Section 20, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

16" Sugar	S 30 W	28 links
18" Sugar	N 35 E	25 links

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. Corner is shown as a spike set in center of road with CAR 37 north and south. Ties:

S. end Culv.	SW	27.15'
N. end Culv.	NW	29.1'

1949 County Highway Engineer's Notebook No. 169 contains road survey for CAR 37 running from south to north on the section line. Corner is shown marked by a hub set in the center of CAR 20. Ties are the same as listed below.

1949 County Surveyor's Record Book 1, page 499, lists ties to a hub by H. G. Elletson:

PP	SW	46.5
SW Cor Sch Hse	NE	155.6

1953 Ties in Notebook 158:

S. end Culv.	SW	53.6'
N. end Culv.	NW	52.75'

(Same ties listed in Notebbok No. 169 dated 1957.)

1987 Paul Wellen, LS 10461, found a 1/2" iron pipe in the intersection of roads north/south and east/west. He replaced it with a cast iron monument and filed a Certificate of Location (#184289).

2008 The County Surveyor's Office searched and found Wellen's 1987 cast iron monument at the intersection of north-south (County Road 61) and east-west (County Road 43) roads. The tie to the SW corner of the old School House measured 156.5 ft., and a PP SW measured 46.2 ft. which agrees with 1949 ties. The Surveyor accepts the position as marking the best evidence and updated ties.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-148336.038

E-521359.016