

Statement of Evidence:

Northeast Corner of Section 21, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

| | | |
|-------------|--------|----------|
| 20" Linden | N 83 W | 11 links |
| 7" Ironwood | N 34 E | 10 links |

1937 County Engineer's Notebook No. 99 contains a road survey for CAR No. 28 running south to north. Notes show corner marked by a spike with town road east and west. Ties:

| | | |
|---------------|----|------|
| Twin Boxelder | NE | 37.4 |
| FP | NW | 49.3 |

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. Corner is shown as a spike set in center of road intersection with CAR 28 running north-south. Ties:

| | | |
|-----------------|----|-------|
| FP | NE | 47.0' |
| NW Cor Twp Hall | SE | 61.8' |

1981 Paul Wollen, LS 10461, found a $\frac{3}{4}$ " I.P. in the centerline of roads north/south and east/west. He replaced it with a cast iron monument. He filed a Certificate of Location (#160213). Notes give a distance of 2720.63 feet to the East $\frac{1}{4}$ corner of Section 16. (Compares well with 1937 distance of 2719.4 feet.) Gives tie of 145.05 feet SW to the NE corner of town hall. (Assume town hall was moved.)

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:
N- 148263.407
E - 526656.891

2003 County Coordinates Obtained by GPS to PK Nail
NAD 83 (1996 Adjustment)
N- 148263.650
E- 526656.573

NOTE: Need to check for ties to see if PK nail is at same position of CIM.