

Statement of Evidence:

H242

Northeast Corner of Section 24, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Elm	N 18 E	40 links
12" W Birch	N 42 W	44 links
8" Maple	S 51 E	84 links
12" W Birch	S 68 1/2 W	21 links

1901 County Surveyor's Record Book A, Map No. 34, contains a survey of Section 13 by John Whilt, which shows this corner

1912 County Surveyor's Record Book 1, page 383 notes the following reference ties:

16" Elm	N 51 1/4 E	75'
6" Maple	N 50 W	50.3'

1912 County Engineer's Notebook No. 2, pages 49 and 50, contain a road survey for SR No. 14 by M. J. Cleveland. Survey starts 928 feet north of this corner. Found old corner post and set iron monument with same ties as listed above.

1915 County Surveyors Record Book 2, page 420 and 421 note an Iron in the road.

1939 County Engineer's Notebook No. 131 contains survey of CAR 32 running south to north on township line and terminating at this corner. Corner is shown as spike in center of road with town road west and southwest. Ties:

PP	NE	39.05
TP	NW	44.35

1941 County Engineer's Notebook No. 152 contains survey of CAR 32 running north on township line from this corner. Corner is shown as spike in center of road with town road west and southwest. Ties same as 1939.

1963 County Surveyor's Record Book 1, page 507, notes a 1" X 2" wood hub with the following reference ties

PP	NE	39.05
TP	NW	43.65

(Notation in County Engineer's Notebook No. 131 contains same ties with note "couldn't find - placed 1x 2 hub.")

1979 William Lunser, LS 9394, found a 3/4" iron pipe at north/south/west centerline.

1988 William Lunser replaced the found 3/4" iron pipe with a cast iron monument and filed a Certificate of Location (#191272). He notes a distance of 2295.16 feet to the North 1/4 corner of Sec 19 in Maywood Township and a distance of 2659.82 feet to the East 1/4 corner Sec 13.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 148491.812
E - 542413.139

2001 Westwood Professional Services, Inc. found a cast iron monument at centerline/centerline.

Benton County Surveyor's Office
Gary H. Stevenson, County Surveyor
Minnesota License No. 12684
Page 2 of 2

2004 Westwood Professional Services, Inc. found CIM.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 148492.041
E- 542412.773