

Statement of Evidence:

Northeast Corner of Section 27, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

12" Linden	N 18 1/2 E	36 links
12" Sugar	S 54 1/2 W	40 links

1907 County Road Book, pages 4-6, contains a road survey by Felix Parent, County Surveyor, for State Road. Survey shows corner found and road run north-south.

1912 County Engineer's Notebook No. 2, page 37, contains a road survey by Cleveland for road running north and east. Notes show post set with ties:

T.P.	S 49-40 E	41
Stone	N 28-30 E	37
T.P.	N 49-45 W	38.2
F. Cor	West	32

Undated County Surveyor's Record Book 1, page 513, notes a gas pipe with the following reference ties:

TP	S 26 W	52.0
TP	S 19 E	73.0
TP	N 39 1/2 E	39.2

1948 C. H. West, LS 932, with MN/DOT, found an iron pin. He set an 8" round by 30" long concrete monument with an aluminum cap and filed a Certificate. Reference ties were R/W iron pipes 180.5 feet NE and SE. MN/DOT alignment map for TH 25 shows corner at intersection of road north-south and road east. Corner is shown 46.7 feet west of POT 895+49.0.

1988 Bruce Skipton, LS 17768, found a zinc cap marked with the section numbers on an 8" round concrete monument, which is 46.9 feet west of the north/south centerline. He filed a Certificate of Location (#191335).

2003 Westwood Professional Services, Inc. found aluminum capped concrete monument as set by West.

County Coordinates Obtained by GPS:

NAD 83 (1996 Adjustment)

N- 142915.430

E- 531923.840