

Statement of Evidence:

H312

Northeast Corner of Section 31, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

14" Aspen	S 66 E	18 links
10" Blk Oak	N 60 E	31 links

1878 County Surveyor's Record Book 1, page 460, Richard Cronk notes a post is marking the corner for a road survey running north and west.

1912 County Engineer's Notebook 1, pages 33 to 37, contains a road survey for SR No. 10 running east –west by M. J. Cleveland. Ties:

12" Elm	NW	52.2'
12" Elm	NE	45.0'

(Also Engineer's Notebook 2, page 23)

1915 County Surveyor's Book 1, page 521, shows ties to an iron monument:

12" Elm	NW	52.2'
12" Elm	NE	45.0'

1970: W end Culvert	NE	61.3
PP	NW	40.95

1935 County Engineer's Notebook No. 87 contains a road survey for SAR No. 4 running from east to west. Corner is shown as an iron pin in 4-way road intersection.

1970 Notation in Notebook No. 87 shows corner found with ties as noted above.

1992 Sidney Williamson, LS, set a cast iron at the centerline of roads north/south and east/west. He filed a Certificate of Location (#213109).

2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline of roads north/south/east/west.

2003 Westwood Professional Services, Inc. found a CIM in the road intersection. Ties checked to PP northwest and to "X" on concrete apron as shown on 1992 Certificate. No evidence was found of 1915 or 1970 ties.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 137640.921

E- 515830.053