

**Statement of Evidence:**

**H332**

Northeast Corner of Section 33, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

13" Sugar	S 70 E	33 links
10" Sugar	N 81 W	17 links

1912 County Engineer's Notebook 1, pages 33-37 contains road survey by M.J. Cleveland for SR No. 10. Notes shows no stake found and set wood stake on old line.  
(Also Engineer's Notebook 2, page 23)

1935 County Engineer's Notebook No. 87 contains a road survey for SAR No. 4 running from this corner west. Corner is shown as a hub and iron in 4-way road intersection. Same ties as 1937.

1937 County Engineer's Notebook No. 99 contains a road survey for CAR No. 28 running from this corner north. Corner is shown as a hub in the center of SAR No. 4 with ties:

Hub	SW	40.2'
Hub	NW	43.2'

1970 County Surveyor's Record Book 1, page 525, notes the following reference ties to an iron and a post:

PP	NE	59.25
PP	NW	56.30
PP	SW	52.5
TP	SE	50.25

1983 David Regan, LS 12236, found a 3/4" solid iron in the centerline of roads north/south and east/west. He filed a Certificate of Location (#167987). Same ties to PP as 1970 ties.

2003 Westwood Professional Services, Inc. found a cast iron monument. No evidence of Regan's 1983 ties as poles had changed.

County Coordinates Obtained by GPS to CIM:

NAD 83 (1996 Adjustment)

N- 137658.479

E- 526568.404

2004 MN/DOT

County Coordinates Obtained by GPS to CIM:

NAD 83 (1996 Adjustment)

N- 137658.506

E- 526568.380