

Statement of Evidence:

East Quarter Corner of Section 6, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Ash	S 74 E	23 links
20" Poplar	S 81 W	36 links

Undated The County Surveyor's Record Book 2, page 19, notes a stake at the corner location.

1915 County Surveyor's Record Book 1, page 17, and Record Book A, Map No. 12 shows a survey for the subdivision of Section 5 by J.P. Soderstrum. He notes he found an old oak stake near a fence corner located from testimony to be the same as Gov't stake at fence corner. It checks OK to a Poplar stump, the stump to the SE is a Basswood, not an Ash, but it checks OK. The old oak stake was replaced with a new stake. He notes the following distances:

39.16 chains (2584.56') to SW Cor Sec 5
45.30 chains (2989.8') to NW Cor Sec 5

He set the 1/16th corners north and south.

2002 Westwood Professional Services, Inc. searched corner area and found a steel T post at the intersection of old, mostly down fence lines running west, south, and north. We measured north 2996.77 feet to the NE corner of Sec. 6 and south 2567.22 feet to the SE corner of Sec. 6. The occupation 1/16th corner to the north fit the proportion of Soderstrum's reasonably well. We found no evidence of the 1/16th corner markers set by Soderstrum. Accepted the steel T post as marking the obliterated corner position as determined by Soderstrum. On 8/30/02 we replaced the steel T post with a cast iron monument and filed a Certificate of Location (#291175)

County Coordinates obtained by GPS (CIM)

NAD 83 (1996 Adjustment)

N-129581.349

E-547652.030