

**Statement of Evidence:**

East Quarter Corner of Section 8, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Elm	S 59 W	50 links
12" Blk Ash	N 11 1/2 E	59 links

1914 County Surveyor's Record Book 1, pages 23and 24, and Record Book A, Map No. 1 shows a survey for the subdivision of Section 8 by J.P. Soderstrum. He found no evidence of the corner and placed corner on true line and equal distant (lost) and notes a stake set for the corner with a distance of 39.88 chains (2632.08 feet) to the NE corner and a distance of 39.87 chains (2631.42 feet) to the SE corner. Ties:

20" Oak	S 33-30 W	18 links
6" Oak	NW	2 links

2005 WSN measured 5270.76 feet between section corners. Compares well with Soderstrum's distance of 79.75 chains (5263.5 feet). Located north-south fence line near corner that fit straight line between approximate section corners. Found no evidence of a corner marker or the 1914 BT's. The area falls in rock pile that has been created from area fields. William Lunser, LS 9394, reported setting the corner. On 9/8/05 we found a  $\frac{1}{2}$ " iron pipe with cap No. 9394 at the lost position, midway and on line between section corners.

County Coordinates to lost position:

NAD 83 (1996 Adjustment)

N- 124279.442

E- 552962.611

2005 Certificate of Location of Government Corner filed as Document Number 332041.