

**Statement of Evidence:**

East Quarter Corner of Section 9, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Maple	S 54 ½ W	28 links
6" Ironwood	N 88 E	7 links

1925 County Engineer's Notebook No. 44, page 9, gives a distance of 2653.3 feet from the NE corner of Section 9 to fence running east.

1935 County Engineer's Notebook No. 92 contains survey for SAR No. 7 running north to south. Notes POT with fence lines east and west. Ties:

Hub E	39.8'
Hub SE	49.85'

Stationing gives distances of 2652.0 feet to the NE corner and 2747.5 feet to the SE corner.

1960 County Engineer's Notebook No. 227 contains survey for SAR No. 7 running south to north. Notes corner as a spike set in center of road with fence lines east and west. Ties:

TP	SW	38.8'
Steel FP	E	55.9'

Stationing gives distances of 2745.0 feet to the SE corner and 2654.5 feet to the NE corner with no angle (POT).

2005 WSN found PK nail in center of north-south road and in line with fence lines east and west. Measured 2651.37 feet to the NE corner and 2747.74 feet to the SE corner. PK nail checks with previous highway information and can be accepted as obliterated corner.

County Coordinates obtained by GPS:

NAD 83 (1996 Adjustment)

N- 124286.058

E- 558261.965