

Statement of Evidence:

J113

East Quarter Corner of Section 11, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

14" Sugar	S 25 W	21 links
10" Oak	S 20 1/2 E	33 links

1902 County Surveyor's Record Book 1, page 29, and Record Book A, Map No. 41, contains a survey of Section 11 by John E. Whilt. This corner is shown at the lost position with 20.33 1/4 chains (1341.95 feet) per 40 acres or 81.33 chains (5367.78 feet) for the east line.

1930 County Engineer's Notebook No. 58 shows road survey by H. G. Elletson running north to south. Corner is not shown but stationing shows east-west 1/4 line fence at 2679.1 feet to the NE corner and 2674.4 feet to the SE corner.

2002 On November 5, 2002 Westwood Professional Services, Inc. searched the corner area, but found no evidence of a corner or ties. We measured 5355.04 feet between section corners, which compared well with the Whilt's survey of 81.33 chains (5367.78 feet). Since Whilt established the corner lost in 1902 we set an iron capped #12684 at the lost position and established reference ties. The corner is set at 1338.76 feet per 40 acres.

County Coordinates
NAD 83 (1996 Adjustment)
N-124305.682
E-568790.979