

Statement of Evidence:

The East Quarter Corner of Section 13, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Tamarack	S 5 1/2 E	110 links
6" Tamarack	S 16 W	140 links

Line trees were noted a a 6" Tamarac North 29.08 chains and a 6" Elm South 23.15 chains.

1965 MN/DNR survey crew notes state that they set corner on line between the section corners at a fence line running east and west.

1988 William Lunser, LS 9394, did not find any monument at the corner, which falls in a swampy area. Found fence line east and west with a 4" x 4" oak post laying down. Placed a 2" x 8 foot iron pipe on line between section corners at the fence line east and west. Placed top of cast iron monument on pipe and set 4" x 4" post next to location. Filed Certificate of Location (Doc. No. 191242). Certificate gives distances of 2702.63 feet to the NE corner and 2677.68 feet to the SE corner.

1996 County Coordinates from John Oliver & Associates by traverse:
NAD 83 (1986 Adjustment)
N- 119176.226
E- 574189.006
Information gives distances of 2702.10 feet to the NE corner and 2677.68 feet to the SE corner with corner on a straight line between section corners.