

Statement of Evidence:

J143

The East Quarter Corner of Section 14, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Linn	S 22 1/2 W	13 links
12" Poplar	N 27 E	26 links

1930 County Engineer's notebook No. 58 shows road survey by H. G. Elletson running north to south. Corner is not shown with a distance of 5334.9 feet for the east line of Section 14.

1965 Survey by the Minnesota Department of Natural Resources shows that this corner was placed on a straight line between the SW and the NW corners of said Section 13 and at the midpoint. The mile measurement was noted at 5338.80 feet.

1988 William Lunser, LS 9394, placed a Benton County cast iron monument at the midpoint between the NE and SE corners of Section 14. The total distance between the NE and SE corners was a distance of 5338.80 feet. A Certificate of Location (#191245) was filed.

2001 Westwood Professional Services, Inc. found a CIM and located it with GPS prior to road reconstruction. CIM fit the lost position, measuring 2669.39 feet to the NE corner and 2669.51 feet to the SE corner. On 11/5/02 set a PK nail at the corner after construction.

County Coordinates to CIM
NAD 83 (1996 Adjustment)
N-118959.901
E-568897.816