

**Statement of Evidence:**

**J183**

East Quarter Corner of Section 18, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

9" Poplar	N 57 E	7 links
9" Poplar	N 20 W	10 links

1914 County Surveyor's Record Book 1, page 41 & 42, and Record Book A, Map No. 2 contains a survey of Section 17 by J.P. Soderstrum. He notes that he found no stake or BT's, but used old fence line west for the corner. Ignored fence line east that was 0.20 chains farther south. He gives distances of 40.56 chains (2676.96 feet) to the NE corner and 40.48 chains (2671.68 feet) to the SE corner. Ties:

16" Elm	SE	62 links
8" Poplar	NE	48 links

2005 WSN found no evidence of a corner marker or BT's and set a spike at intersection of fence lines east, west, and north. Measured 2679.15 feet to SE corner and 2679.41 feet to the NE corner. Spike is basically midway and 4.45 feet east of a straight line between section corners and within 3 feet of a proportion to Soderstrum's distance in 1914. Accepted fence intersection as the best evidence of the corner's obliterated position and replaced the spike with a cast iron monument.

County Coordinates obtained by side-tie:

NAD 83 (1996 Adjustment)  
N- 119021.901  
E- 547893.544

2005 Westwood Professional Services, Inc. set a cast iron monument over a found/removed spike at the intersection of tree lines to the north and west, also noting a fence line east.

NAD 83 (1996 Adjustment)  
N- 119021.901  
E- 547893.544