

Statement of Evidence

J193

East Quarter Corner of Section 19, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Poplar	N 14 E	28 links
3" Oak	S 60 W	6 links
5" Poplar	S 1 E	14 links

1915 County Surveyor's Record Book 1, page 45, and Record Book A, Map No. 11 shows J.P. Soderstrum did a survey of Section 19. He set the corner by lost methods on line and midway between the section corners. He measured 80.54 chains (5,316.64 feet) between section corners and set a wood stake for the corner. He notes a fence line from the west 0.07 chains (4.62 feet) north of where he set the corner and that residents claim the fence line is at the 1/4 line, according to a stake set by Parent in 1889. However, Parents notes show corner set lost and claims to have ignored the fence line and therefore Soderstrum also did.

2002 Westwood Professional Services, Inc. searched corner area at intersection of roads north, south, and east and fence line west. No monument was found. We measured 5318.80 feet between section corners, which compared well with Soderstrum. The lost position fits the occupation of roads and fence line. On December 4, 2002 Westwood Professional Services, Inc. set an iron capped #12684 at the lost position, as J.P. Soderstrum did in 1915.
County Coordinates to set corner.
NAD 83 (1996 Adjustment)
N-113684.408
E-547974.679