

Statement of Evidence:

J223

The East Quarter Corner of Section 22, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

10" Ash	N 41 E	146 links
9" Ash	N 5 1/2 W	209 links

Undated Roll E-4, of the MN/DOT Highway plans for TH 95, show the corner is marked by an iron monument and is 2683.7 feet from the NE corner Sec 27.

1914 County Surveyor's Record Book 1, pages 53-54, and Record Book A, Map No. 19, notes a survey of Section 23 by JP Soderstrum. He notes a distance of 40.65 chains (2682.90 feet) to the NE and SE corners Sec 22. He also notes a fence line east 12 links north and he set a stake equidistant and on true line.

1926 County Surveyor's Record Book 1, pages 51 and 52, and Map No. 48 contains a survey of Section 22 by Harry Elletson. (Notes in Notebook 48) Elletson notes a post at the corner as set by Soderstrum and a distance of 2682 feet to the NE and SE corners of Sec 22.

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north. Corner is shown as a hub set in center of road with fence lines east and west. Gives a distance of 2683.3 feet to the NE corner.

2008 The County Surveyor's Office searched and found a cast iron monument approximately 5 ft. west of centerline. Position falls 2683.70 ft. south of the NE corner and 2684.48 ft. north of the SE corner. These distances agree with the above mentioned surveys and plans. The Surveyor accepted the cast iron position and set new ties.

County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-113649.846
E-563797.410