

Statement of Evidence:

J273

The East Quarter Corner of Section 27, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

6" Blk Ash	N 19 W	55 links
10" Tamarack	S 59 1/2 E	5 links

1901 County Surveyor's Record Book 1, page 61, and Record Book A, Map No. 40, is a survey of the subdivision of Section 27 by John E. Whilt. He notes a distance of 40.55 chains (2676.3 feet) to the NE corner and a distance of 40.34 chains 2662.44 feet) to the SE corner.

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north on section line. Corner is shown as a hub set in center of road with fence lines east and west. Ties:

Cor. FP	E	22.05'
FP	SE	32.7'

Stationing gives distances of 2666.8 feet to the SE corner and 2676.9 feet to the NE corner.

1990 Paul Wellen, LS 10461, set a cast iron monument at the centerline of roads north/south and a fence line east/west. He filed a Certificate of Location (#201452).

2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline of roads north/south and a fence line west.

2008 Westwood Professional Services, Inc. found a cast iron monument at the centerline of roads north/south and a fence line west.

County Coordinates
NAD 83 (1996 Adjustment)
N-108294.960
E-563891.614