

Statement of Evidence:

J293

The East Quarter Corner of Section 29, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Blk Oak	S 71 W	133 links
8" Bur Oak	S 33 E	284 links

1920 County ties to iron:

6" Br. Oak	SW	87.78
8" Br. Oak	SE	187.40

1929 County Surveyor's Record Book 1, page 65 and County Surveyor's Record Book A, Map No. 49, shows a survey of Section 28 by M.B. Lang. Corner is shown marked by an iron shaft with distances of 2640 feet to the NE and SE corners of Section 29. Ties:

8" R. Oak	S 28 E	29.6 feet
12" W. Oak	N 81 W	34.7 feet

2008 The Benton County Surveyor's Office searched and found a 1" iron pipe with cap inscribed "RLS 16095", at 1 ft. ± above the ground. The reference trees from M.B. Lang's 1929 survey were also found to be in existence and were in agreement with the pipe position. Comparing distances between the Northeast and Southeast corners of the Section gives 2641.00 ft. to the NE corner and 2641.50 ft. to the SE corner, which is in harmony with Lang's 1929 measurements. The Deputy Surveyor left the iron pipe in place and accepts said iron pipe as the best evidence.

County Coordinates
NAD 83 (1996 Adjustment)
N- 108,300.237
E- 553329.499