

Statement of Evidence:

J343

The East Quarter Corner of Section 34, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

13" Poplar	N 46 E	25 links
15" W Oak	S 44 W	53 links

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north on section line. No corner is shown, but stationing shows east-west fence at 2670 feet north of the SE corner.

1987 Paul Wellen, LS 10461, found a $\frac{1}{2}$ " I. Pipe in the centerline of a north/south road and a fence line east/west. He replaced it with a cast iron monument and filed a Certificate of Location (#184284). Measured 2653.06 feet south to the SE corner of Section 34.

2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline of a north/south road and an occupation line east/west.

2008 The Benton County Surveyor's Office searched and found the cast iron monument set by Wellen in 1987. The position as found gives a distance of 2652.98 ft. from the SE corner, which agrees with Wellens distance of 2653.06. Position agrees with occupation lines to the east and west. Accepted position as the best evidence and updated ties shown in Wellen's certificate dated 1987.

Benton County Coordinates obtained with GPS
NAD 83 (1996 Adjustment)
N-102973.326
E-563848.864