

**Statement of Evidence:**

**J021**

The North Quarter of Section 2, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
- |             |        |          |
|-------------|--------|----------|
| 8" Sugar    | N 2 W  | 26 links |
| 6" Ironwood | S 36 W | 22 links |
- 1901 County Surveyor's Record Book 2, page 454, and Record Book A, Map No. 35 shows a survey of Section 35, 37-28 by John E. Whilt. He notes a distance of 40.03 chains (2641.98 feet) to the SE Cor Sec 35 and a distance of 40.135 chains (2648.91 feet) to the SW Cor of Sec 35.
- 1912 County Engineer's Notebook 1, pages 37 to 42, contains a survey for SR No. 10 by M. J. Cleveland. Notes show corner as a spike with stationing giving distances of 2652 feet to the NW corner and 2653 to the NE corner of Section 2.
- 1939 County Engineer's Notebook No. 125 contains survey of CAR 42 running east to west on township line. Corner is shown as a spike in center of road with fence lines north and south. Ties:
- |    |    |       |
|----|----|-------|
| TP | N  | 19.9' |
| PP | NE | 32.9' |
- Stationing gives distances of 2647.0 feet to the NE corner and 2650.9 feet to NW corner with no angle.
- 1979 Paul Wellen, LS 10461, set a cast iron monument and the intersection of a fence line south and the centerline of County Road 51 (running east and west). He filed a Certificate of Location (#155136) and notes a distance of 2656.86 feet to the NW corner Sec 2 and a distance of 2645.77 feet to the NE corner Sec 2.
- NOTE: Wellens' position fits within 2 feet of the 1901 proportion and can be accepted as marking the obliterated corner position.
- 2008 The County Surveyor's Office searched and found a cast iron monument, as set by Wellen in 1979. Distances to the NW Cor. and the NE Cor. give 2656.77 ft. and 2645.72 ft., respectively. Position agrees within 2.04 ft. of the proportioned 1901 position and is accepted as marking the obliterated corner position. Ties were updated.

County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-132753.038  
E-566075.024