

Statement of Evidence:

J061

The North Quarter Corner of Section 6, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Blk Ash	N 31 W	40 links
6" Basswood	S 5 E	12 links

A 16" Elm line tree was noted West 21.10 chains.

1901 County Surveyor's Record Book 2, page 446, and Record Book A, map No. 42, contains a survey of Section 31 by John Whilt. Survey notes a distance of 40.02 chains (2641.32') to the NE Cor Sec 6 and a distance of 36.81 chains (2429.46') to the NW Cor Sec 6.

1939 County Engineer's Notebook No. 125 contains survey of CAR 42 running east to west on township line. No corner is shown, but notes fence north and south at approximate corner being 2653.0 feet from the NE corner and 2431.3 feet from the NW corner.

2002 Westwood Professional Services, Inc. found no evidence of a corner monument at the centerline of County Road 51 (running east and west) and occupation fence lines north and south. No evidence remains of original trees or 1915 ties. We set temporary corner at occupation and measured 2641.34 feet to the NE corner of Section 6 and 2435.92 feet to the NW corner of Section 6. These distances check reasonably well with the 1901 survey. Accepted the center of the road and fence lines as marking the obliterated position of the corner. Set a ½ " iron pipe and took ties and filed a Certificate of Location (#291174).
County Coordinates obtained by GPS to set ½ " iron pipe:
NAD 83 (1996 Adjustment)
N-132506.041
E-544835.561