

Statement of Evidence:

The North Quarter Corner of Section 7, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

| | | |
|-------------|--------|----------|
| 12" Blk Oak | S 61 E | 25 links |
| 6" Ironwood | N 12 E | 26 links |

2002 No resurvey information was found on this corner in the Benton County records.

2002 Westwood Professional Services, Inc. searched for evidence of this corner and found old fence lines running north, west, and east. No evidence of a corner marker or bearing trees were found. From the fence corner, we measured 2630.44 feet west to the NW corner of Sec. 7 and 2596.76 feet east to the NE corner of Sec. 7. The distance of 5226.96 feet between section corners is 157.50 feet longer than the GLO distance. The fence corner was found to 21 feet south of a straight line between section corners and 125 feet east of the lost position. We tied into occupation lines in the interior of Section 6, but these did not support either position. We accepted the fence corner as marking the obliterated position of the corner.

On November 5, Westwood Professional Services, Inc. set a cast iron monument at the obliterated position of the section corner and established reference ties. County Coordinates to set corner.

NAD 83 (1996 Adjustment)
N-127209.439
E-545148.717