

Statement of Evidence:

J081

North Quarter Corner of Section 8, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

18" Oak	S 12 W	25 links
5" Ironwood	N 15 E	22 links

1914 County Surveyor's Record Book 1, pages 23 and 24, and Record Book A, Map No. 1, shows a survey for the subdivision of Section 8 by J. P. Soderstrum. He notes a fence line at 39.34 chains (2596.44 feet) east of the NW corner.

1915 County Surveyor's Record Book 1, pages 17 and 18, and Record Book A, Map No. 12, contains a survey for the subdivision of Section 5 by J.P. Soderstrum. He found an old oak stump SE that checked for GLO BT. He drove a 1/2" gas pipe 4' long at the corner location. He notes a distance of 38.98 chains (2572.68 feet) to the SE corner Section 5, a distance of 39.42 chains (2601.72 feet) to the SW corner Section 5, and a distance of 85.34 chains (5632.44 feet) to the North 1/4 corner Sec. 5.

2002 Dennis Pederson, LS 16095, re-set the corner based on evidence of fence lines.

2005 WSN found 1" iron pipe with cap No. 16095 on east-west fence with fence line running north. Measured 2601.66 feet to the NW corner set by Pederson and 2572.90 feet to the approximate NE corner marked by fence lines and 5627.57 feet to the North 1/4 corner of Section 5. Distances agree with Soderstrum's 1915 survey.

County Coordinates obtained by GPS:
NAD 83 (1996 Adjustment)
N-126971.392
E-550339.518

2011 The Benton County Surveyor's Office found an iron pipe capped 16095 set over a 2" pinched top iron pipe in the east-west centerline of a gravel road and on fences north and south at the CS1/16 of Section 5-36-28. The distance between the found irons and the found iron pipe at this corner position fit flat with 1915 distance.