

Statement of Evidence:

North Quarter Corner of Section 19, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

16" Bur Oak	S 24 W	160 links
6" Black Oak	N 11 E	54 links

1915 County Surveyor's Record Book 1, pages 45 and 46, and Record Book A, Map No. 11 shows J.P. Soderstrum did a survey of Section 19. At the corner he found stumps of both Gov't BT's and drove oak stake level with the ground and took new BT's as follows:

10" R. Oak	S 9-15 W	70 links
10" Basswood	N 27-45 W	75 links

Notes show total mile at 78.76 chains (5198.16 feet) with 39.85 chains (2630.10 feet) to NW corner and 38.91 chains (2568.06 feet) to NE corner.

2002 Westwood Professional Services, Inc. searched corner area at intersection of road east-west and fence lines north-south. No monument or evidence of bearing trees was found. We measured 5197.48 feet between section corners, which compared well with Soderstrum's. We considered the corner to be obliterated based on the Soderstrum survey and established the corner using the center of east-west road and proportionate distances to Soderstrum's survey between the NE and NW corners of Section 19. On December 4, 2002 Westwood Professional Services, Inc. set an iron capped #12684 at a proportionate distance from the NW and NE corners Sec. 19 based on Soderstrum's survey. The corner is 2567.72 feet to the NE corner Sec 19 and 2629.76 feet to the NW corner Sec 19. Corner is 10.02 feet south of a straight line between section corners.

County Coordinates to set corner.

NAD 83 (1996 Adjustment)

N-116531.872

E-545339.338