

**Statement of Evidence:**

**J331**

North Quarter Corner of Section 33, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
- |             |        |           |
|-------------|--------|-----------|
| 10" Bur Oak | S 73 W | 235 links |
| 8" W Oak    | N 29 W | 281 links |
- 1920 County ties:
- |             |    |        |
|-------------|----|--------|
| 10" Bur Oak | SW | 155.10 |
| 8" W. Oak   | NW | 185.46 |
- 1929 County Surveyor's Record Book 1, page 63 and Record Book A, Map No. 49 show a survey of Section 28 by M. B. Lang. Corner is shown marked by a stake with a distance of 2654 feet north to the center of Section 28.
- 1933 County Engineer's notebook No. 70 shows road survey by H. G. Elletson. Corner is shown in line with fences running north and south. Stationing gives distances of 2627.3 feet to the NW corner and 2629.2 feet to the NE corner.
- 2005 Sam DeLeo, LS 40341, found no evidence of the corner and established the corner at the lost position, midway and on a straight line between section corners. He set a cast iron monument.  
County Coordinates to set corner:  
NAD 83 (1996 Adjustment)  
N- 105661.293  
E- 555938.733