

Statement of Evidence:

J341

The North Quarter of Section 34, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey set a wood post with bearing trees noted as:

6" Blk Ash	S 64 E	28 links
9" Bur Oak	N 29 E	16 links

- 1901 County Surveyor's Record Book A, Map No. 40 is a survey of Section 27 by John Whilt. Distance of 40.00 chains to SW corner and 40.07 chains to SE corner of Section 27.

- 1993 Dennis Taylor, LS 15233, established corner by proportionate distance between section corners using Whilt's 1901 survey distances. He set a cast iron monument and filed a Certificate of Location (Doc. No. 212585).

- 2008 The Benton County Surveyor's Office searched and found the cast iron monument as set by Dennis Taylor in 1993. Position agrees with distances from Whilt's 1901 survey, where we measured 2645.29 ft. (40.08 ch.) to the SE Cor. of Sec. 27 (Whilt 40.07 ch.) and 2640.79 ft. (40.01 ch.) to the SW Cor. of Sec. 27 (Whilt 40.00 ch.). Accepted position as the best evidence and updated ties shown on Taylor's 1993 Certificate of Location.

Benton County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-105643.841
E-561209.589