

**Statement of Evidence:**

The Northeast Corner of Section 2, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

12" Basswood	N 14	11 links
8" Basswood	N 31 1/2 E	3 links
12" Basswood	S 36 W	40 links
10" W Ash	N 1 W	25 links

1900 County Surveyor's Record Book A, Map No. 39 shows John Whilt did a survey of Section 1.

1901 County Surveyor's Record Book 2, page 454, and Record Book A, Map No. 35 shows a survey of Section 35, 37-28 by John E. Whilt. Survey notes a distance of 38.96 chains to the E Cor Sec 35 (Maywood) and a distance of 40.03 chains to the S Cor Sec 35 (Maywood).

1912 County Engineer's Notebook 1, pages 37 to 42 contains a survey for SR No. 10 by M. J. Cleveland. Notes show stake and iron found and set stone 20" long on end at side of iron pin, pin east and made ties.

6" Ash S 52 E 55.5'	T.P.	N 46 1/2 E	32.1'
HighPt. Rock (Grey Granite)	N 61 E		91.3'

1930 County Engineer's notebook No. 58 shows road survey by H. G. Elletson running north to south. Corner is shown as a stone and iron with ties:

T.P.	SW	50.9'	F.P.	NW	41.0'
------	----	-------	------	----	-------

1939 County Engineer's Notebook No. 125 contains survey of CAR 42 running east to west on township line. Corner is shown as a stone in center of 4-way road intersection. Ties:

G.P.	NE	57.8	F.P.	NW	58.2
------	----	------	------	----	------

1956 County Surveyor's Record Book 2, page 11 notes there is a stone and an iron at the corner with the following reference ties, (which is also noted on the J.P. Sodestrum survey in October 12, 1916.)

T.P.	SW	68.7
T.P.	SE	113.30

1979 Paul Wellen, LS 10461, set a cast iron monument at the centerline of County Road 9 (running north and south and County Road 51 (running east and west) and filed a Certificate of Location (#160217).

1979 Paul Wellen notes on Certificate of Location (#155136) the distance between the NE and the N 1/4 Corners of Section 2 is 2645.77 feet.

2001 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerlines of County Road 9 (running north and south) and 35<sup>th</sup> Street NE (running east and west). We checked tie sheet and noted changes in ties.

2002 County Coordinates obtained by GPS (CIM)  
NAD 83 (1996 Adjustment)  
N-132775.491  
E-568720.665

***CORNER NEEDS TO BE EXCAVATED!***