

Statement of Evidence:

J032

The Northeast of Section 3, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded:

6" Blk. Oak	S 28 W	29 links
6" Elm	N 26 1/2 W	55 links
8" Bur Oak	N 28 E	40 links
10" Basswood	S 72 E	20 links

1901 County Surveyor's Record Book A, Map No. 35 shows a survey of Section 35, 37-28 by John E. Whilt.

1912 County Surveyor's Record Book 2, page 383 gives ties to an iron monument:

TP	N 50 1/2 E	31 feet
NW Cor House	S 51 1/2 E	77.3 feet
NE Cor School	S 64 1/2 W	165 feet

1912 County Engineer's Notebook 1, pages 37 to 42 contains a survey for SR No. 10 by M. J. Cleveland. States corner is iron monument (Parents) in north-south road and lists same ties as above.

1916 County Surveyor's Record Book 1, page 11 (and on Record Book A, Map No. 21), JP Soderstrum notes an iron stake in the intersection of roads on the township line. County Surveyor's Record Book 1 page 13 also notes a survey done by in 1916. He notes the following reference ties to an iron

TP	N 50 1/2 E	47 links
NW Cor House	S 51 1/2 E	117 links
NE Cor School House	S 64 1/2 W	250 links

1939 County Engineer's Notebook No. 125 contains survey of CAR 42 running east to west on township line. Corner is shown as an iron in center of 4-way road intersection. Ties:

FP	NE	41.35
18" Cottonwood	SE	41.45

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north on section line with survey terminating at this corner. Same information as in Notebook No. 125.

1979 Paul Wellen, LS 10461, set a cast iron monument at the location of a found red head in the centerline of County Road 51 and County Road 67. He filed a Certificate of Location (#155138). He gives a tie of 78.78 feet SE to NW corner of House.

2003 Westwood Professional Services, Inc. found a cast iron monument and obtained coordinates. Corner appears to be good but still need to check for 1912 and 1916 ties. Wellen's 1979 ties show NW corner of House SE 78.78. (Soderstrum's tie: 77.22 feet)

2008 The County Surveyor's Office searched and found a cast iron monument as set by Wellen in 1979. The Surveyor did not find remains of the 1912 and 1916 ties. Position agrees with centerline intersection of north-south and east-west roads. Wellen's 1979 tie to "NW corner of house" agrees with 1912 ties. Position is accepted as marking the obliterated position. Ties were updated.

County Coordinates by GPS to CIM
NAD 83 (1996 Adjustment)
N- 132731.683
E- 563418.335