

Statement of Evidence:

J092

Northeast Corner of Section 9, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as:

4" Blk Ash	S 13 W	23 links
9" Blk Oak	N 36 E	25 links

1916 County Surveyor's Record Book 1, page 13, J.P. Soderstrum notes a stake at the intersection of roads, said to be the original by landowners, as stake was in its location before survey for road.

9" Elm	N 11-30 E	175
14" Ash	W	60

He notes a distance of 40.62 chains (2680.92 feet) to the East 1/4 corner Sec 4 and a distance of 40.72 chains (2687.52 feet) to the North 1/4 corner Sec 10.

1925 County Engineer's Notebook No. 44, page 9, lists ties to square granite monument:

15" Elm	West	39.5'
8" Elm	NE	115.4'

1935 County Engineer's Notebook No. 92 contains survey for SAR No. 7 running north to south. Notes corner as granite monument with town road east and fence west. Ties:

18" Elm	W	39.5'
6" Elm	NW	48.9'

1960 County Engineer's Notebook No. 227 contains survey for SAR No. 7 running south to north. Notes corner as a granite monument found in center of road with town road east and fence line west being 3 feet north. Ties:

18" Elm	W	39.5'
6" Elm	NW	48.9'
12" W. Oak	NW	79.4'

Notes in 1963 replaced with iron and same ties as below.

1963 County Surveyor's Records in Book 1, page 25 note the following ties to an iron:

12" Twin Elm	NW	83.2'
16" Oak	SW	60.7'
PP	NE	54.9'

2003 Westwood Professional Services, Inc. found a 1/2 " iron pipe with cap marked No. 14700 (Paul Schoborg) in centerline of CSAH 7 (north-south) and 45th Street NE (east). Took the following ties, which fit well with 1963 ties:

36" Oak	SW	60.17
PP	NE	55.25

County Coordinates by GPS - 1/2 iron pipe

NAD 83 (1996 Adjustment)

N- 126936.828

E- 558205.484

2005 On 4/20/05 dug corner location with Benton County Highway Dept. backhoe and down 2.8 feet and below surface pipe found in 2003, we found 8" x 10" flat top cut Granite Monument with 3/4" iron rod 2.3 feet long alongside and over the top.

2007 Set a 1/2" x 14" iron pipe with cap "19552" at the 2003 coordinates of the found stone and 1/2" iron pipe.