

Statement of Evidence:

J112

The Northeast Corner of Section 11, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

24" Linn	S 55 1/2 W	24 links
20" Linn	S 69 E	23 links

1900 County Surveyor's Record Book A, Map No. 39, contains a survey of Section 1 by John Whilt.

1902 County Surveyor's Record Book 1, page 29, and Record Book A, Map No. 41 contains a survey of Section 11 by John Whilt. He notes corner marked by a stone.

1916 County Surveyor's Record Book 1, page 29, Soderstrum notes that this corner is a stone about 8"X10" irregular shaped with an 'X' on top with the following reference ties.

F.P.	NE	44.0
T.P.	SE	39.40
Mailbox Post	S	50.2

1930 County Engineer's Notebook No. 58 shows road survey by H. G. Elletson running north to south. Corner is shown as a stone monument with ties:

F.P.	NE	44.0'
T.P.	SE	39.4'

1979 Paul Wellen, LS 10461, set a Benton County cast iron monument at the centerline intersections of a township road and County Road 9 and filed a Certificate of Location (#160216). He notes a distance of 2561.82 feet between the North 1/4 corner and NE corner of Section 11 per Certificate of Location (#155141).

2001 On August 28, 2001 Westwood Professional Services, Inc. found a cast iron monument at the centerline intersections of County Road 9 (running north and south) and 45th Street NE (running east and west). We checked tie sheet and noted changes in ties.

2002 On May 1, 2002 Westwood Professional Services, Inc. dug under the cast iron monument in a hole 12' X 12' and 4' deep, to natural ground. We did not find any monuments. On October 31, 2002 Westwood Professional Services, Inc. set an iron capped #12684 at the location of the found cast iron monument.

County Coordinates by GPS
NAD 83 (1996 Adjustment)
N-126982.394
E-568725.785