

Statement of Evidence:

Northeast Corner of Section 12, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Ironwood	S 9 W	28 links
18" Elm	S 70 E	18 links
12" Basswood	N 63 E	29 links
10" W. Ash	N 50 W	30 links

1900 County Surveyor's Record Book 1, page 9, and Record Book A, Map No. 39, shows a survey by John Whilt of Section 1. No information is given, but corner is shown with distances north and west.

1996 County Coordinates from John Oliver & Associates by traverse:
NAD 83 (1986 Adjustment)
N- 127282.322
E- 574087.177
Position was assumed corner in center of road intersection with roads north-south and west with a fence line east.

2004 10/19/04 excavated corner area with Dennis Pederson, LS 16095, Mille Lacs County Surveyor, in center of north-south road and in line with road west and fence line east. Down 2 feet below roadbed, we found a 5" round by 12" long piece of an oak wood stake. Stake was badly rotted. Since the wood stake fit occupation lines, we accepted the stake as marking the corner position. We set a standard Benton County cast iron monument at the location of the found stake. Hole excavated with backhoe was approximately 12 feet east-west and 20 feet north-south. No other evidence of a corner marker was found.
County Coordinates obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 127268.628
E- 574093.441

(Note: JOA coordinates in 1996 must have been to a computed position.)