

Statement of Evidence:

J132

Northeast Corner of Section 13, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Tamarack	N 50 E	6 links
6" Tamarack	S 73 E	8 links
6" Tamarack	S 11 W	27 links
6" Tamarack	N 45 W	14 links

Line trees were noted as a 6" Tamarack south 10.92 chains and a 6" Tamarack north 21.67 chains.

1910 Mille Lacs County records show S. L. Kennedy found the corner when surveying Section 7, 36-27 and notes that "Gov't corner – new tam. stake, NE Gov't tree standing, open, readable and SW Gov't tree down.

1917 Mille Lacs County records show that O. E. Garrison made a survey of the line between Sections 7 and 18 and notes post and Gov't bearings at this corner.

1965 Minnesota DNR did a survey in Section 13 in which their notes state: "set corner from County records at intersection of roads and fence south". They placed a MN/DNR cast iron monument.

1988 William Lunser, LS 9394, found a RR spike in road intersection based on MN/DNR record. He replaced the spike with a cast iron monument and filed a Certificate of Location (Doc. No. 191244). Gives distance of 2662.0 feet to the North 1/4 corner of Section 13.

1994 John Oliver, LS 8194, Mille Lacs County Surveyor, found CIM during road survey for CSAH No. 7.
County Coordinates from John Oliver & Associates by traverse
NAD 83 (1986 Adjustment)
N- 121878.290
E- 574174.308

1998 MN/DNR found CIM down 1 foot and set spike above. John Oliver found spike and filed Certificate of Location in Mille Lacs County. (Doc. No. 877)

2004 County Coordinates obtained by GPS to broken CIM:
NAD 83 (1996 Adjustment)
N- 121878.819
E- 574174.449

2008 The County Surveyor's Office searched and found a cast iron monument at the intersection of an east-west gravel road and a gravel road leading to the north. Distance to the North 1/4 Cor. gives 2662.00 feet which agrees with Lunser's 1988 measurement. Updated ties.

Benton County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 121878.663
E- 574174.368