

Statement of Evidence:

J222

The Northeast Corner of Section 22, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

13" Blk Ash	N 69 E	12 links
20" W Oak	N 34 W	33 links

1914 County Surveyor's Record Book 1, pages 53-54, and Record Book A, Map No. 19, contains a survey of Section 23 by J. P. Soderstrum. He notes he found an oak stake which was set by Parent in survey of town road. Also found old Oak N 34 W 33 links. Made new ties:

14" Elm	N 44-30 W	75 links
TP	N 38-30 E	58 links
12" Elm	S 50 E	71 links

Note: ties also listed in County Engineer's Notebook 44 from 1925.

1926 County Surveyor's Record Book 1, pages 51 and 52, and Map No. 48 contains a survey of Section 22 by Harry Elletson. (Notes in Notebook 48) He states that he found stake left by Soderstrum. He notes the following reference ties to iron monument:

FP	NW	38.2
TP	NE	39.4

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north on section line. Corner is shown as a hub set in center of 4-way road intersection. Ties:

FP	NW	38.2'
TP	NE	39.4'

1962 County highway reference ties to an iron over a rock:

PP	NW	52.2
Fen Cor	SW	48.5
15" Twin Elm	SE	85.6

2007 Westwood found a 1" solid iron rod. Ties from earlier years were not found.

Coordinates obtained by GPS to 1" solid iron rod
NAD 83 (1996 Adjustment)
N-116332.188
E-563712.038

2010 The Benton County Surveyor's Office found the iron rod, which fits resurvey distances in all four directions within a couple of feet. We verified the 2007 coordinates and created reference ties as shown.