

Statement of Evidence:

J262

The Northeast Corner of Section 26, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

14" Blk Ash	N 19 E	456 links
16" Elm	S 34 W	533 links

1914 County Surveyor's Record Book 1, page 59, and Record Book A, Map No. 19 contains a survey by of Section 23 by JP Soderstrum. He notes he found old post in center of road. Mr. Ambretson claims the post to be in original location of old corner. He set a stone on end for corner.

Newer ties by County Highway Department on same page:

Fen Cor	NW	31.3
Fen Cor	NE	47.9

1970's Roll E-4, of MN/DOT Highway plans for TH 95, shows the corner was assumed at the center of roads north, east, and west.

1988 Bruce Skipton, LS 17768, found a large spike at the centerline of roads north/east/west that fit with MN/DOT's assumed location. He set a cast iron monument over the spike and filed a Certificate of Location (#191326).

2008 The County Surveyor's Office searched and found a railroad spike below the bituminous on State Highway 95. The position fits Skipton's ties from 1988 and aligns with an old fence line trailing south of the Highway. The Surveyor accepted Skipton's position and set a PK nail with a washer flush with the surface and ties were updated.

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N-110902.718

E-569077.932

NOTE: It is recommended that the stone monument referenced in County Surveyor's Record Book 1, page 59, and Record Book A, Map No. 19, by JP Soderstrum, be searched for during any future State Highway 95 construction in this area.