

Statement of Evidence:

J292

The Northeast Corner of Section 29, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

20" Bur Oak	S 40 W	1582 links
14" Bur Oak	S 84 W	1287 links

1929 County Surveyor's Record Book 1 on pages 63 to 65 Record Book A, Map No. 49 contains a survey of Section 28 by MB Lang. Ties to 4" oak stake:

Fence Corner	N	25.2
Fence Post	S	26.3
Other tie:		
Hub	S	33.0

1942 MN/DOT notes call for field stone down 4.0 feet at intersection of east-west road and fence lines north-south.

1948 Roll O-11, of the MN/DOT Highway plans, show the corner is a 1/2" I.P set over a field stone at the centerline of a road east/west and a fence line north/south with the following reference ties.

3 rd FP	SE	62.8
2 nd FP	S	46.6
Cor FP	S	41.4

Corner is 14.3 feet south of new centerline.

1949 MN/DOT recovered corner from 3 reference ties in 1942.

1966 MN/DOT notes call for an iron pin down 6" over field stone.

1970's Roll E-4, of the MN/DOT Highway plans, show the corner is marked by an I.P. is 14.3 ft south of new centerline with the following reference ties.

N & D PP	NE	49.55
N & D COR FP	SW	40.98
N & D FP	NE	80.4

1970 MN/DOT notes call for iron pin with 3 iron pin reference ties prior to construction.

1972 MN/DOT notes show iron pin set after construction with additional ties.

1997 James Nielson, LS 11865, with MN/DOT recovered 3/4" iron pin and reference ties and set a cast iron monument. Filed Certificate of Location (No. 261578)

2003 County Coordinates obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N- 110941.162
E- 553350.048