

Statement of Evidence:

J355

The South Quarter Corner of Section 35, Township 36 North, Range 28 West,
Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a post for this corner and bearing trees were recorded:

10" Elm	N 4 3/4 W	121 links
8" Blk Ash	N 62 E	140 links

A line tree was noted as a 14" W Oak West 26.55 chains.

1917 County Surveyor's Record Book 1, page 7 contains survey notes by N. Drolson of survey for judicial road between Sherburne and Benton Counties.

1975 John Oliver, LS 8194, Sherburne County Surveyor, found a stone as mentioned in notes by S. L. Kennedy in 1917. Stone was found leaning. Stone was straightened and tied out. Iron pipes were set on the north and south sides flush with the stone.

2000 Sherburne County Surveyor placed a CIM over the granite monument and updated the Certificate of Location.

2004 Certificate of Survey by David Regan, LS 12236, shows CIM at corner 2669.36 feet east of the SW corner.

2008 The Benton County Surveyor's Office searched and found a Sherburne County cast iron monument, as set by the Sherburne County Surveyor in 2000. The Surveyor accepts the history of the position and updated ties from the Sherburne County Surveyor's certificate of location.

Benton County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 100267.414

E-566509.815