

Statement of Evidence:

J334

Southeast Corner of Section 33, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office survey set a post for this corner and bearing trees were recorded.
- | | | |
|--------------|----------|----------|
| 12" Basswood | N 84 ½ E | 58 links |
| 24" W Oak | N 41 W | 37 links |
| 12" W Ash | S 63 W | 58 links |
| 12" Elm | S 22 E | 26 links |
- Line trees were noted as a 10" Blk Oak East 17.03 chains and a 12" W Oak West 19.92 chains.
- 1917 County Surveyor's Record Book 1, page 7, contains survey notes by N. Drolson of survey for judicial road between Sherburne and Benton Counties. He states that he planted a granite stone at this corner.
- 1935 County Engineer's Notebook No. 92 contains survey for SAR No. 7 running north to south and terminating at this corner. Notes corner as a spike. Ties (also listed in County Surveyor's Record Book 1, page 73, ties to stone):
- | | | |
|--------|----|--------|
| 8" Oak | NE | 72.3' |
| Hub | NW | 60.85' |
- 1976 John Oliver, LS 8194, Sherburne County Surveyor, re-established corner in centerline intersection of roads. He set a cast iron monument and filed Certificate of Location (Doc. No. 140254-Sherburne). States position fits prorating of County Surveyor Williams' distances in 1899 across north line of Section 3 and fits occupation in Section 4.
- 1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:
- | | |
|-----|------------|
| N- | 100359.534 |
| E - | 558525.243 |
- 2000 Sherburne County Surveyor found CIM and updated Certificate.
Benton County Coordinates converted from Sherburne County Coordinates:
NAD 83 (1986 Adjustment)
N- 100359.53
E- 558525.54
- 2005 Sam DeLeo, LS, found CIM and obtained County Coordinates by GPS.
NAD 83 (1996 Adjustment)
N- 100359.750
E- 558524.900
- 2005 On 6/29/05 Sherburne County Surveyor, Mike Trunk, excavated corner area and found the granite monument.
Benton County Coordinates converted from Sherburne County Coordinates:
NAD 83 (1986 Adjustment)
N- 100360.85
E- 558530.46

NOTE: Granite monument was found approximately 5 feet east of the CIM.