

Statement of Evidence:

The Southeast Corner of Section 34, Township 36 North, Range 28 West, Glendorado Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a post for this corner and bearing trees were recorded.

| | | |
|-------------|------------|----------|
| 6" W Oak | N 29 E | 29 links |
| 18" Blk Oak | N 50 W | 36 links |
| 10" W Oak | S 33 1/2 W | 44 links |
| 14" Elm | S 53 1/2 E | 14 links |

Line trees were noted as a 14" W Oak East 13.78 chains and a 8" Blk Oak West 22.50 chains.

1917 County Surveyor's Record Book 1, page 7, contains survey notes by N. Drolson of survey for judicial road between Sherburne and Benton Counties. He states that he found corner marked by a stone in north-south road set by Sherburne County. New ties:

| | | |
|---------|--------|--------------|
| 18" Elm | NW | 69 links |
| TP | S 40 W | 64 1/2 links |

1939 County Engineer's Notebook No. 123 contains survey of CAR 39 running south to north on section line. Corner is shown as a granite monument in 4-way road intersection. Ties:

| | | |
|-----|----|-------|
| TP | SW | 41.1' |
| Elm | NW | 44.8' |

1970 County Surveyor's Record Book 1, page 75, notes stone in north-south road with ties:

| | | |
|---------|----|--------|
| 30" Elm | NW | 45.55' |
| PP | NE | 82.5' |

(Noted in Notebook No. 123)

1972 John Oliver, LS 8194, Sherburne County Surveyor, found standard granite monument over old wood stake and set a cast iron monument. Certificate of Location filed in Sherburne County. (Note: Oliver's ties slightly different than 1970, but Oliver's are to face.)

2000 Sherburne County Surveyor found CIM and updated Certificate.
County Coordinates converted from Sherburne County Coordinates
NAD83 (1986 Adjustment)
N – 100320.00
E – 563841.508

County Coordinates
NAD 83 (1996 Adjustment)
N-
E-