

**Statement of Evidence:**

**J354**

The Southeast Corner of Section 35, Township 36 North, Range 28 West, Glendorado Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a post for this corner and bearing trees were recorded.

|            |            |           |
|------------|------------|-----------|
| 12" Poplar | N 30 1/4 E | 421 links |
| 12" Poplar | N 51 1/2 W | 762 links |

1917 County Surveyor's Record Book 1, page 7 contains survey notes by N. Drolson of survey for judicial road between Sherburne and Benton Counties. He states that this corner was marked by a stone in north-south road set by Sherburne County. New ties: 18 " Elm NW 69 links and Tel. Pole S 40 W 64.5 links.  
(Book says Section 35, but believe it is the south line of Section 36. Same info for SE corner Sec. 34.)

1972 John Oliver, LS 8194, Sherburne County Surveyor, found standard granite monument and set a cast iron monument. Filed Certificate of Location in Sherburne County.

2000 Sherburne County Surveyor found CIM and updated Certificate.  
County Coordinates converted from Sherburne County Coordinates  
NAD83 (1986 Adjustment)  
N – 100219.35  
E – 569161.69

2008 The Benton County Surveyor's Office searched and found the cast iron monument as set over the granite monument in 1972 by John Oliver. The Surveyor accepted the monument and updated ties.

Benton County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-100219.717  
E-569161.136